## WHAT IS CLAIMED IS:

1	1.	Α	method	for	collecting	information	from	а

- 2 telecommunications network for a portal, comprising the steps
- 3 of:
- 4 receiving at least one service level from the
- 5 portal, the at least one service level associated with at
- 6 least one subscriber;
- determining at least one parameter that corresponds
- 8 to the at least one service level;
- 9 collecting at least one item of information that
- 10 relates to the at least one subscriber in accordance with the
- 11 at least one parameter; and
- forwarding the at least one item of information to
- 13 the portal.

- 1 2. The method according to claim 1, wherein the at
- 2 least one item of information comprises a location indication
- 3 of a mobile equipment associated with the at least one
- 4 subscriber.
- 1 3. The method according to claim 1, wherein the at
- 2 least one subscriber comprises a plurality of subscribers,
- 3 the plurality of subscribers comprising a group of
- 4 subscribers related according to the portal.
- 1 4. The method according to claim 1, wherein the at
- 2 least one service level is received in a transaction
- 3 agreement between the portal and the telecommunications
- 4 network.

- 1 5. The method according to claim 1, wherein the at
- 2 least one parameter comprises at least one of an accuracy
- 3 range, a response time, a network node/entity, and a polling
- 4 of vs. proactive triggering by a designated network
- 5 node/entity variable.
- 1 6. The method according to claim 1, wherein said step
- of collecting at least one item of information that relates
- 3 to the at least one subscriber in accordance with the at
- 4 least one parameter comprises the steps of:
- 5 polling a network node/entity for the at least one
- 6 item of information; and
- 7 receiving, responsive to said step of polling, the
- 8 at least one item of information from the network
- 9 node/entity.
- The method according to claim 6, wherein the
- 2 network node/entity comprises a home location register or a
- 3 mobile positioning center.

- 1 8. The method according to claim 1, wherein said step
- 2 of collecting at least one item of information that relates
- 3 to the at least one subscriber in accordance with the at
- 4 least one parameter comprises the steps of:
- instructing a network node/entity to proactively
- 6 trigger transmission of the at least one item of information;
- 7 and
- 8 receiving, responsive to said step of instructing,
- 9 the at least one item of information from the network
- 10 node/entity.
- 1 9. The method according to claim 8, wherein the
- 2 network node/entity comprises at least one of a mobile
- 3 equipment, a subscriber identity module (SIM), and a SIM
- 4 application.

- 1 10. The method according to claim 1, wherein the portal comprises at least one of an Internet portal, an information
- 3 service provider, a data server, and a world wide web (WWW)
- 4 site.
- 1 11. The method according to claim 1, wherein said step
- 2 of determining at least one parameter that corresponds to the
- 3 at least one service level comprises the step of mapping the
- 4 at least one service level in a data structure to an entry
- 5 comprising a plurality of parameters, the plurality of
- 6 parameters including the at least one parameter.

1	12. A method for collecting information from a
2	telecommunications network for a portal, comprising the steps
3	of:
4	receiving from the portal a service level
5	corresponding to desired location information, the service
6	level associated with at least one subscriber;
7	comparing the received service level to a plurality
8	of stored service levels, the plurality of stored service
9	levels including a first service level and a second service
10	level;
11	if the received service level matches the
12	first service level, then requesting the desired
13	location information via a first scheme;
14	if the received service level matches the
15	second service level, then requesting the desired
16	location information via a second scheme;
17	receiving the desired location information via at
18	least one of the first scheme and the second scheme; and

- 19 forwarding the received desired location 20 information to the portal.
  - 1 13. The method according to claim 12, wherein the
  - 2 portal comprises at least one of an Internet portal, an
  - 3 information service provider, a data server, and a world wide
  - 4 web (WWW) site.
  - 1 14. The method according to claim 12, wherein the at
  - 2 least one service level is received in a transaction
  - 3 agreement between the portal and the telecommunications
  - 4 network, the transaction agreement directed to the at least
  - 5 one subscriber.
  - 1 15. The method according to claim 12, wherein the first
  - 2 service level includes a first accuracy range and the second
  - 3 service level includes a second accuracy range, the first
- 4 accuracy range differing from the second accuracy range.

1 16. The method according to claim 12, wherein the first 2 service level includes a first response time and the second 3 service level includes a second response time, the first 4 response time differing from the second response time.

17. The method according to claim 12, wherein the first service level includes a first network node/entity and the second service level includes a second network node/entity, the first network node/entity differing from the second network node/entity.

1 18. The method according to claim 17, wherein the first 2 network node/entity comprises a mobile positioning center and 3 the second network node/entity comprises a mobile equipment.

19. The method according to claim 17, wherein the first 2 network node/entity comprises a home location register node 3 and the second network node/entity comprises a mobile 4 equipment.

- 20. The method according to claim 12, wherein the first service level includes a first mobile equipment transmission medium and the second service level includes a second mobile equipment transmission medium.
- 21. The method according to claim 20, wherein the first mobile equipment transmission medium comprises a short message service (SMS) format and the second mobile equipment transmission medium comprises an unstructured supplementary service data (USSD) format.

1 The method according to claim 12, wherein the first 2 scheme comprises polling a network node/entity for the 3 desired location information, and the second scheme comprises 4 at least one of (i) retrieving a previously-received-from-a-5 mobile-equipment desired location information and (ii) 6 pushing an application module to a mobile equipment and 7 awaiting the desired location information to be received from 8 the mobile equipment.

- 1 23. An arrangement for facilitating the collecting of
- 2 target information from a telecommunications network for a
- 3 portal, comprising:
- a first logic module, said first logic module
- 5 capable of communicating with the portal to receive at least
- one service level, the at least one service level associated
- 7 with at least one subscriber;
- a second logic module, said second logic module
- 9 capable of communicating with the telecommunications network
- 10 to receive target information therefrom;
- 11 a data structure, said data structure including a
- 12 plurality of entries, each entry of the plurality of entries
- including a service level and at least one parameter; and
- a third logic module, said third logic module
- capable of comparing the at least one service level with each
- entry of the plurality of entries of said data structure to
- 17 determine a corresponding entry.

- 1 24. The arrangement according to claim 23, wherein the
- 2 arrangement comprises a business-to-business (B2B) engine.
- 1 25. The arrangement according to claim 23, wherein at
- 2 least two of the first logic module, the second logic module,
- 3 and the third logic module comprise a single larger
- 4 consolidated logic module.
- 1 26. The arrangement according to claim 23, wherein the
- 2 at least one parameter comprises a network node/entity, and
- 3 wherein at least one of said second logic module and said
- 4 third logic module is configured to orchestrate a
- 5 communication regime with the network node/entity to thereby
- 6 receive the target information therefrom.